

Revision Date: 2016-08-23

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

RB HR PIB 2300

Product Name Supplier RB HR PIB 2300 RB Products Inc. 740 Bradfield Road Houston TX 77060 Phone: 1 (281) 992-3500 Fax: (281) 992-7525

Transportation Emergency Response Website Other product information (800) 424-9300 (CHEMTREC) http://www.rbproductsinc.com sales@rbproductsinc.com

SECTION 2: HAZARDS IDENTIFICATION

CLASSIFICATION

Not classified as hazardous according to 29 CFR 1910.1200 (2012).

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS#	Amount
Polyisobutylene	Trade secret	100% weight

Not that the chemical identity of some or all of the above components is considered confidential business information and is being withheld as permitted by 29 CFR 1910.1200 and various State Right-To-Know Laws.

SECTION 4: FIRST AID MEASURES

Eye: No specific first aid measures are required. As a precaution, remove contact lenses, if worn, and flush eyes with water. If heated material should splash into eyes, flush eyes immediately with fresh water for 15 minutes while holding the eyelids open. Remove contact lenses, if worn. Get immediate medical attention.

Skin: No specific first aid measures are required. As a precaution, remove clothing and shoes if contaminated. To remove the material from skin, apply a waterless hand cleaner, mineral oil, or petroleum jelly. Then wash with soap and water. Discard contaminated clothing and shoes or thoroughly clean before reuse. If the hot material gets on skin, quickly cool in water. See a doctor for extensive burns. Do not try to peel the solidified material from the skin, or use solvents or thinners to dissolve it. The use of vegetable oil or mineral oil is recommended for removal of this material from the skin. **Ingestion**: No specific first aid measures are required. Do not induce vomiting. As a precaution, get medical advice.

Inhalation: No specific first aid measures are required. If exposed to excessive levels of material in the air, move the exposed person to fresh air. Get medical attention if coughing or respiratory discomfort occurs.

Most important symptoms and effects, both acute of delayed IMMEDIATE SYMPTOMS AND HEALTH EFFECTS

Eye: Not expected prolonged or significant eye irritation. If this material is heated, thermal burns may result from eye contact.

Skin: Contact with the skin is not expected to cause prolonged or significant irritation. Contact with the skin is not expected to cause an allergic skin response. Not expected to be harmful to internal organs if absorbed through the skin. If this material is heated, thermal burns may result from skin contact.

Ingestion: Not expected to be harmful if swallowed.

Inhalation: The inhalation toxicity of this substance has not been determined.



Revision Date: 2016-08-23

SECTION 5: FIREFIGHTING MEASURES

FIRE CLASSIFICATION: OSHA Classification (29 CFR 1910.1200): Not classified by OSHA as flammable or combustible. **Flammable Properties:**

Flash Point: (Cleveland Open Cup) 190°C (356°F) Minimum. **Auto-ignition:** No data available.

EXTINGUISHINGMEDIA: Use water fog, foam, dry chemical or carbon dioxide (C02) to extinguish flames. **PROTECTION OF FIRE FIGHTERS**:

Fire Fighting Instructions: This material will burn although it is not easily ignited. For fires involving this material, do not enter any enclosed or confined fire space without proper protective equipment, including self-contained breathing apparatus.

Combustion Products: Highly dependent on combustion conditions. A complex mixture of airborne solids, liquids, and gases including carbon monoxide, carbon dioxide, and unidentified organic compounds will be evolved when this material undergoes combustion.

SECTION 6: ACCIDENTAL RELEASE MEASURE

Protective Measures: Eliminate all sources of ignition in vicinity of spilled material.

Spill Management: Stop the source of the release if you can do it without risk. Contain release to prevent further contamination of soil, surface water or groundwater. Clean up spill as soon as possible, observing precautions in Exposure Controls/Personal Protection. Use appropriate techniques such as applying non-combustible absorbent materials or pumping. Where feasible and appropriate, remove contaminated soil. Place contaminated materials in disposable containers and dispose of in a manner consistent with applicable regulations. If heated material is spilled, allow it to cool before proceeding with disposal methods.

SECTION 7: HANDLING AND STORAGE

Precautionary Measures: Do not get in eyes, on skin, or on clothing. Avoid contact of heated material with eyes, skin, and clothing. Wash thoroughly after handling.

General Handling Information: The maximum handling temperature is 115°C. Avoid contaminating soil or releasing this material into sewage and drainage systems and bodies of water.

Static Hazard: Electrostatic charge may accumulate and create a hazardous condition when handling this material. To minimize this hazard, bonding and grounding may be necessary but may not, by themselves, be sufficient. Review all operations which have the potential of generating and accumulating an electrostatic charge and/or a flammable atmosphere (including tank and container filling, splash filling, tank cleaning, sampling, gauging, switch loading, filtering, mixing, agitation, and vacuum truck operations) and use appropriate mitigating procedures. For more information, refer to OSHA Standard 29 CFR

1910.106, 'Flammable and Combustible Liquids', National Fire Protection Association (NFPA 77,

'Recommended Practice on Static Electricity', and/or the American Petroleum Institute (API) Recommended Practice 2003, 'Protection Against Ignitions Arising Out of Static, Lightning, and Stray Currents'. The maximum storage temperature is 80°C.

Container Warnings: Container is not designed to contain pressure. Do not use pressure to empty container or it may rupture with explosive force. Empty containers retain product residue (solid, liquid, and/or vapor) and can be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. They may explode and cause injury or death. Empty containers should be completely drained, properly closed, and promptly returned to a drum reconditioner or disposed of properly.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

GENERAL CONSIDERATIONS:



Revision Date: 2016-08-23

Consider the potential hazards of this material (see Section 3), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

ENGINEERING CONTROLS: Use in a well-ventilated area.

PERSONAL PROTECTIVE EQUIPMENT

Eye/Face Protection: No special eye protection is normally required. Where splashing is possible, wear safety glasses with side shields as a good safety practice. If this material is heated, wear chemical goggles or safety glasses or a face shield.

Skin Protection: No special protective clothing is normally required. Where splashing is possible, select

protective clothing depending on operations conducted, physical requirements and other substances in the workplace. Suggested materials for protective gloves include: Nitrile Rubber, Silver Shield, Viton. If this material is heated, wear insulated clothing to prevent skin contact if engineering controls or work practices are not adequate to prevent skin contact.

Respiratory Protection: No respiratory protection is normally required.

Use a positive pressure air-supplying respirator in circumstances where air-purifying respirators may not provide adequate protection.

No applicable occupational exposure limits exist for this material or its components.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Color	Colorless	Solubility	Insoluble in water
Physical State	Liquid	Freezing Point	No Data Available
Odor	No Data Available	Specific Gravity	0.9076 @ 15.6°C (60°F)
рН	Not Applicable	Density (15°C)	0.9071 kg/1
Vapor Pressure	No data available	Viscosity (100°C)	1600 cSt
Vapor Density (Air= 1)	No data available	Coefficient of Therm. Expansion I °F	0.00031
Boiling Point	No Data Available	Evaporation Rate	No Data Available

Attention: the data below are typical values and do not constitute a specification.

SECTION 10: STABILITY AND REACTIVITY

Chemical Stability: This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.

Conditions to Avoid: Do not exceed handling and storage temperatures listed in SDS Section 7 (Handling and Storage). **Incompatibility With Other Materials**: May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.

Hazardous Decomposition Products: None known (None expected)

Hazardous Polymerization: Hazardous polymerization will not occur.

SECTION 11: TOXICOLOGICAL INFORMATION

Eye Irritation: The eye irritation hazard is based on evaluation of data for similar materials or product components. **Skin Irritation**: The skin irritation hazard is based on evaluation of data for similar materials or product components.

Skin Sensitization: The skin sensitization hazard is based on evaluation of data for similar materials or product components.

Acute Dermal Toxicity: The acute dermal toxicity hazard is based on evaluation of data for similar materials or product components.



Revision Date: 2016-08-23

Acute Oral Toxicity: The acute oral toxicity hazard is based on evaluation of data for similar materials or product components.

Acute Inhalation Toxicity: The acute inhalation toxicity hazard is based on evaluation of data for similar materials or product components.

No product toxicology data available.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY

This material is not expected to be harmful to aquatic organisms. The ecotoxicity hazard is based on an evaluation of data for the components or a similar material.

MOBILITY

No data available.

PERSISTENCE AND DEGRADABILITY

This material is not expected to be readily biodegradable. The biodegradability of this material is based on an evaluation of data for the components or a similar material. The product has not been tested. The statement has been derived from products of a similar structure and composition.

POTENTITAL TO BIOACCUMULATE

Bioconcentration Factor: No data available.

Octanol/Water Partition Coefficient: No data available.

SECTION 13: DISPOSAL CONSIDERATIONS

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste,

federal law requires disposal at a licensed hazardous waste disposal facility.

SECTION 14: TRANSPORT INFORMATION

The description shown may not apply to all shipping situations. Consult 49CFR, or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name) and mode-specific or quantity-specific shipping requirements.

DOT Shipping Description: NOT REGULATED AS HAZARDOUS MATERIAL FOR TRANSPORTATION UNDER 49 CFR **IMOIIMDG Shipping Description**: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDER THE IMDG CODE **ICAOIIATAS hipping Description**: NOT REGULATED AS DANGEROUS GOODS FOR TRANSPORT UNDERICAO

SECTION 15: REGULATORY INFORMATION

EPCRA 311/312 CATEGORIES:

- 1. Immediate (Acute) Health Effects: NO
- 2. Delayed (Chronic) Health Effects: NO
- 3. Fire Hazard: NO
- 4. Sudden Release of Pressure Hazard: NO
- 5. Reactivity Hazard: NO

REGULATORY LISTS SEARCHED:

01-1=1ARC Group 1 03=EPCRA 313 01-2A=IARC Group 2A 04=CA Proposition 65 01-2B=IARC Group 28 05=MA RTK



Revision Date: 2016-08-23


02=NTP Carcinogen 06=NJ RTK 07=PA RTK No components of this material were found on the regulatory lists above. **CHEMICAL INVENTORIES**:


All components comply with the following chemical inventory requirements: AICS (Australia), DSL (Canada), EINECS (European Union), ENCS (Japan), IECSC (China), KECI (Korea), PICCS (Philippines), TSCA (United States).

SECTION 16: OTHER INFORMATION

Hazardous Materials Information System (USA)

Health Hazard	0
Fire Hazard	1
Reactivity Hazard	0





(0-Least, 1-Siight, 2-Moderate, 3-High, 4-Extreme, PPE:- Personal Protection Equipment Index recommendation, *-Chronic Effect Indicator). These values are obtained using the guidelines or published evaluations prepared by the National Fire Protection Association (NFPA) or the National Paint and Coating Association (for HMIS ratings).

The information in this SDS pertains only to the product as shipped.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.